

WORK WITH TCP/IP CONNECTION STATUS

SYSTEM RS043

TYPE OPTIONS, PRESS ENTER.
 3 = ENABLE DEBUG 4 = END 5 = DISPLAY DETAILS 6 = DISABLE DEBUG
 8 = DISPLAY JOBS

OPT	REMOTE ADDRESS	REMOTE PORT	LOCAL PORT	IDLE TIME	STATE
—	9.130.69.80	34266	TELNET	000:16:36	ESTABLISHED
—	9.130.69.108	3032	TELNET	000:03:05	ESTABLISHED
—	9.130.69.236	1069	*	005:07:15	*UDP
—	9.130.69.236	1073	*	005:07:15	*UDP
—	192.168.5.2	1031	*	005:07:15	*UDP
8	192.168.5.2	1031	5033	000:29:37	ESTABLISHED

F5 = REFRESH F11= DISPLAY BYTE COUNTS F13 = SORT BY COLUMN
 F14 = DISPLAY PORT NUMBERS F22 = DISPLAY ENTIRE FIELD
 F24 = MORE KEYS

Fig. 2A

WORK WITH TCP/IP CONNECTION STATUS

SYSTEM RS043

CONNECTION TYPE *TCP
 LOCAL ADDRESS..... 192.168.5.1
 LOCAL PORT..... 5033
 REMOTE ADDRESS..... 192.168.5.2
 REMOTE PORT..... 1031

TYPE OPTIONS, PRESS ENTER.
 5= WORK WITH JOB

OPT	NAME	USER	NUMBER
—	RS043NWS	QSYS	07435
—	RS043NWS	QSYS	07439

F3 = EXIT F5 = REFRESH F6 = PRINT F9 = COMMAND LINE
 F12 = CANCEL

Fig. 2B




Fig. 3




Fig. 4